

APPLICATION FOR UNITED STATES LETTERS PATENT

FOR

**METHOD, APPARATUS AND SYSTEM FOR
IMPROVED CONTENT MANAGEMENT AND DELIVERY**

Inventor(s): **Stephen C. Roderick**

Prepared by:

BLAKELY SOKOLOFF TAYLOR & ZAFMAN, LLP
12400 Wilshire Boulevard, 7th Floor
Los Angeles, California 90025
(503) 684-6200

"Express Mail" label number EL034435616US

Date of Deposit September 18, 2000

**METHOD, APPARATUS AND SYSTEM FOR
IMPROVED CONTENT MANAGEMENT AND DELIVERY**

COPYRIGHT NOTICE

5 A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise expressly reserves all rights whatsoever in said copyright works.

10 BACKGROUND OF THE INVENTION

1. Field of the Invention

 The present invention relates to the field of data processing over data networks and, in particular, to a method, apparatus and system for improved content management and
15 delivery.

2. Background Information

 As computer technology has evolved, so too has the use of data networks to communicatively couple computer systems together enabling them to communicate with one
20 another. Those skilled in the art will appreciate that data networks may be configured in a number of alternative network topologies, employing any number of alternative communication protocols. From small peer-to-peer networks, to local area networks (LAN),

wide area networks (WAN) and enterprise networks (sometimes referred to as an intranet), to global data networks. One of the more popular of such global data networks is colloquially referred to as the Internet, an Internetworking of governmental, educational and commercial networks and servers throughout the world.

5 Once the domain of scholars and computer researchers, the introduction and acceptance of the HyperText Markup Language (HTML) and the HyperText Transfer Protocol (HTTP) associated with the World Wide Web (WWW) initiative effectively opened the Internet to anyone with an appropriately configured computer system. With the increased accessibility brought about with the WWW, data networks such as the Internet have evolved
10 into a limitless collection of information for those with the computer savvy to access them.

One of the criticisms of the Internet, in particular, is that the wealth of information that is theoretically available on the Internet is not easily identified and retrieved by a typical user. Until recently, this difficulty in accessing the eclectic collection of information available on the Internet has not really been a problem, as many netizens¹ rely on search
15 engines and the like to locate information of interest. Simplistically speaking, search engines search the meta-tags and text of a number of web pages in an effort to identify the information of interest. Until recently, the use of such search engines has proven acceptable as a means of identifying information on the web.

Recently, however, the Internet has evolved to support electronic commerce,
20 sometimes referred to as e-commerce. Electronic commerce sites on, for example, the

Internet are presented in the form of publicly accessible web pages which place the stock, availability and pricing information of their products online. A typical e-commerce site may be thought of as being comprised of at least two parts, a first part which is comprised of the HTML document to create the graphical user interface (GUI) on the Internet, and a second

5 part comprised of a database housing the product information, i.e., stock/availability, and pricing information. The GUI front end provides the user with a means of searching for product information, stock or availability, and pricing by entering search terms or a query list, which is then used to access and retrieve the appropriate information from the database for display to the user. Accordingly, it typically requires at least two searches, often more, to

10 identify the particular information of interest on the Internet. This makes it difficult, at best, for many netizens to find product information as it is often buried in databases hidden from search engines. One solution to make product information more readily accessible is to forego the product databases and have programmers generate HTML code for dedicated web pages for each product. One drawback of such a solution, however, is that substantial

15 investments have been made to put together the current product databases. To simply forego using current product databases would be a costly solution, not to mention the substantial cost of generating dedicated web pages for each product. However, companies staking their commercial success on the e-commerce business paradigm will attest that the current difficulty conducting e-commerce is resulting in lost opportunity and unrealized profit for

20 many e-commerce sites.

¹ Those skilled in the art will appreciate that a new vocabulary has evolved to describe the evolving sociology

Thus, an improved method, apparatus and system for identifying, managing and delivering information content, e.g., product information, is required, unencumbered by the deficiencies and inherent limitations commonly associated with data networks and the network devices of the prior art. It will be apparent to those skilled in the art, from the description to follow, that the present invention achieves these and other desired results.

03869.P001C

of the Internet, wherein a netizen is a citizen on the Internet, i.e., an Internet user.

SUMMARY OF THE INVENTION

In accordance with the teachings of the present invention, a method, apparatus and system for managing and delivering informational content over a data network is presented.

In particular, in accordance with one embodiment of the present invention, an apparatus

5 comprising a storage medium and a communicatively coupled processor are presented. The

storage medium has stored therein a plurality of executable instructions which, when

executed, implement an information server which, upon receiving a request including a

resource identifier for an information page/directory that may or may not exist, constructs

and issues queries to retrieve the requested information and dynamically generates

10 instructions to create the requested information page for provision to a requesting client if the information page does not exist.

BRIEF DESCRIPTION OF DRAWINGS

The present invention will be described by way of exemplary embodiments, but not limitations, illustrated in the accompanying drawings in which like references denote similar elements, and in which:

5 **Figure 1** illustrates a block diagram of an example data network incorporating the teachings of the present invention;

Figure 2 illustrates a block diagram of an example server incorporating the teachings of the present invention, in accordance with one embodiment of the present invention;

10 **Figure 3** illustrates a flow chart of an example method for managing the availability of information content incorporating the teachings of the present invention;

Figure 4 illustrates a block diagram of an example server incorporating the teachings of the present invention, in accordance with an alternate embodiment of the present invention;

15 **Figure 5** illustrates a flow chart of an example method for tracking the source of referrals to information sources in accordance with one aspect of the present invention;

Figure 6 graphically illustrates an example product database suitable for use in accordance with the teachings of the present invention;

Figure 7 graphically illustrates an example marketing report generated in accordance with one aspect of the present invention; and

20 **Figure 8** illustrates a block diagram of a storage medium having stored therein executable instructions for implementing the teachings of the present invention, in accordance with an alternate embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

In the following description, various aspects of the present invention will be described. However, it will be apparent to those skilled in the art that the present invention may be practiced with only some or all aspects of the present invention. For purposes of explanation, specific numbers and configurations are set forth in order to provide a thorough understanding of the present invention. However, it will also be apparent to those skilled in the art that the present invention may be practiced without these specific details. In other instances, well known features are omitted or simplified for clarity.

Reference in the specification to “one embodiment” or “an embodiment” means that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, the appearances of the phrase “in one embodiment” appearing in various places throughout the specification are not necessarily all referring to the same embodiment.

With reference to **Figure 1**, an operating environment within which the teachings of the present invention may be practiced will be developed more fully in accordance with the block diagram of example data network **100**. As provided in **Figure 1**, data network **100** is comprised of a plurality of clients, e.g., **102** and **112** that are communicatively coupled to a plurality of information sources, e.g., servers **108**, **116** and **117**, and databases **110** and **118**, via one or more data networks, e.g., data network **106**, as shown. In one embodiment, data network **106** represents a global data network such as the Internet, while in alternate embodiments, data network **106** represents an enterprise network or an Intranet. In

accordance with the teachings of the present invention to be described more fully below, an information server enabled with the teachings of the present invention, e.g., server **108**, invokes an instance of an information server which, upon receiving a request including a resource identifier for an information page/directory that does not exist, constructs and issues
5 one or more queries to accessible information resources to retrieve the requested information and dynamically generates instructions to create the requested information page for provision to the requesting client. In accordance with the teachings of the present invention, if the information page/directory identifier by the received request does exist, the requested information page is provisioned to the requesting client.

10 In one exemplary embodiment, to be developed more fully below, the resource identifier is comprised of an industry standard product identifier (ISPID), wherein the information server dynamically generates the instructions to create the requested information page to provision to the requesting client, in response to receiving a request from the client comprising the ISPID as the resource identifier for an information page that does not exist.

15 Thus, those skilled in the art will appreciate that a server incorporating the teachings of the present invention for dynamically generating instructions to create an information page in response to receiving a request comprised of an industry standard product identifier, effectively place their entire inventory of products on the data network at uniquely addressable locations (e.g., web sites, web pages, etc.), without having to resort to multiple
20 intermediate information pages generating common gateway interface (CGI) scripts, or the un-memorable, lengthy URLs commonly associated with the prior art. Accordingly, the

present invention enables a vendor to utilize the information contained in their current product databases, protecting the substantial investment made to generate such databases, while offering improved visibility of their product line to their current or potential customer base.

5 As shown in **Figure 1**, clients **102** and **112** can be any of a wide range of computing devices known in the art which enable a user to access information using a messaging protocol via data network **106**. In one embodiment, for example, clients **102** and **112** execute a browser application which supports communication with a remote server, e.g., server **108**, via data network **106** and gateway server **104**, while in other embodiments, the client is
10 directly coupled to data network **106**. In one embodiment, the messaging protocol utilized is the HyperText Transfer Protocol (HTTP) and the information page is a web page. In another embodiment, the messaging protocol is the File Transfer Protocol (FTP), and the information page is a document file. In either instance, the request for the information page includes a document identifier comprised of the industry standard product identifier, without requiring
15 the user to enter any additional language that is otherwise supported by the messaging protocol, e.g., query scripts and the like. In one embodiment, clients **102** and/or **112** are computer systems, while in an alternate embodiment, they are an electronic appliance, e.g., a webTV™ Internet Terminal available from Sony Electronics, Inc. of Park Ridge, NJ, that enables one to utilize the resources of data network **106** without the need of a full-featured
20 computer system.

Each server **108**, **116** and **117** is typically a computer system which can be accessed by clients via data network **106** either directly, or through a firewall **114** or other gateway server. As used herein, each server incorporating the teachings of the present invention, e.g., server **108**, includes one or more information pages (e.g., HyperText Markup Language (HTML) compatible documents, or web-pages), which can be accessed via any of a number of appropriate messaging protocols for display by an appropriate user agent (e.g., browser) operating on a requesting client, e.g., client **102**. In accordance with the teachings of the present invention, to be described more fully below, a server incorporating the teachings of the present invention includes an agent which, upon receiving a request including an industry standard product identifier for an information page or directory that does not exist, constructs and issues commands or queries to search for and retrieve from accessible resources (e.g., databases) information corresponding to the product associated with the industry standard product identifier included in the received request, and generates executable instructions to create the requested information page for provision at the requesting client. In alternate embodiments, the ISPID is a multiple listing service (MLS) identifier for real estate, a vehicle identification number (VIN) identifier for automobiles, a stock-keeping unit (SKU) identifier for various manufactured products, or a universal identifier (UID) for other products. Thus, a merchant utilizing the teachings of the present invention may well use one of the above identified product codes, or variations thereof, to place information regarding their products on the internet, at uniquely addressable locations, without the need of generating individual information pages/directories for that information prior to receiving the

request for information. That is, the present invention enables a merchant to leverage their pre-existing information resources to dynamically create information pages for each of their products at uniquely addressable locations on a data network using their product code as the address.

5 As alluded to above, data network **106** is a combination of multiple conventional hardware components, including computer systems, routers, repeaters, gateways, and switches interconnected, potentially throughout the world, with wireline and wireless (e.g., satellite, terrestrial, and the like) communication connections. These hardware components are organized to provide multiple logical levels of networks, which route data from one
10 computer system to another. According to one implementation, data is transferred between computer systems using the well-known Transmission Control Protocol/Internet Protocol (TCP/IP) protocol. Data is generally transferred between network elements in units commonly referred to as "packets" or "datagrams".

The communication links illustrated in **Figure 1** may be any of a wide range of
15 conventional wireline and wireless communication media, and may be different for different clients **102**, hosts **108** and network devices **104**. For example, a communication link may be a cable, a fiber optic cable, or may represent a nonphysical medium transmitting electromagnetic signals in the electromagnetic spectrum. Additionally, a wireless communication link may also include any number of conventional routing or repeating
20 devices, such as satellites or electromagnetic signal repeaters or basestations.

Having introduced the operating environment within which the teachings of the present invention may be practiced with reference to **Figure 1**, above, an example server incorporating the teachings of the present invention will now be developed with reference to **Figure 2**.

5 With reference to **Figure 2**, a block diagram of an example server incorporating the teachings of the present invention is depicted, in accordance with but one embodiment of the present invention. In accordance with the illustrated example embodiment of **Figure 2**, server **200** is shown comprising one or more processor(s) **202** and a storage medium/device **206** including executable instructions to implement information server **203** and mining agent **204** incorporating the teachings of the present invention. In certain embodiments, storage medium **206** also includes instructions to implement a statistical database **205** which is used to compile and maintain a statistical history of marketing effectiveness, as shown. In addition to the foregoing, server **200** also includes network interface **208** and input/output (I/O) ports **210** each communicatively coupled to processor(s) **202** as shown. Thus, in 15 accordance with one embodiment of the present invention, server **200** may well be incorporated into data network **100** as one or more of servers **108**, **116** and/or **117** facilitating the perception that an end user has direct access to information pages containing product information utilizing industry standard product identifiers in the information request when, in fact, such information pages may not exist prior to the request.

20 As used herein, network interface **208** enables server **200** to communicate with remote devices over communicatively coupled data networks. In one embodiment, network

interface **208** facilitates receipt of requests in any of a number of messaging protocol formats for information from remote clients. In one embodiment, the requesting client formulates a request in accordance with the HTTP messaging protocol by generating a uniform resource locator (URL) address including a resource identifier comprised of an industry standard product identifier (ISPID). Thus, network interface **208** is intended to represent any of a number of communication interfaces supporting any of a number of alternative communication/data networking protocols commonly known to those in the data networking arts. In particular, network interface **208** is intended to represent any of a number of wireline and wireless communication media through which these interfaces may communicate with remote clients, client subnetworks, and data network **106**. Similarly, input/output ports **210** enable server **200** to communicate with directly coupled devices such as, for example, disk drives, modems, and the like. Network interfaces and I/O ports are well known in the art and need not be described further.

Storage medium/device **206** is intended to represent any of a number of alternative storage media commonly known in the art. In one embodiment, for example, storage medium/device **206** is a memory device, or an array of such devices, such as a random access memory (RAM), flash memory device, or the like. In one embodiment, storage medium/device **206** is a magnetic storage media such as a hard disk, redundant array of inexpensive disks (RAID) system, re-writeable compact disk, tape media, or the like. In one embodiment, to be described more fully below, storage medium **206** includes executable instructions which, when executed by processor(s) **202** implement information server **203**,

mining agent **204** and, optionally, statistical database **205**. As will be described in greater detail below, information server **203** generates instructions to create an information page for provision to a requesting client in response to a request for an information page which may or may not exist. More specifically, upon receiving a request including a resource identifier for an information page/directory that does not exist, processor(s) **202** implementing information server **203** invoke an instance of mining agent **204** which determines if the received information request includes an resource identifier comprised of an industry standard product identifier (ISPID) and, if so, constructs and issues search commands in an effort to retrieve the requested information from accessible resources. As will be described more fully below, mining agent **204** may well access local and/or remote information resources via I/O ports **210** and network interface **208**, respectively.

In accordance with one embodiment of the present invention, processor(s) **202** implementing information server **203** and mining agent **204** work cooperatively to implement the many aspects of the present invention. As used herein, processor(s) **202** are intended to represent any of a number of microprocessors, microcontrollers, programmable logic devices (PLDs), application specific integrated circuits (ASICs) and the like known in the art. In accordance with the teachings of the present invention, processor(s) **202** implementing information server **203** respond to requests for information received from remote client(s) via data network **106** and network interface **208**. In particular, in accordance with one aspect of the present invention to be described more fully below, upon receiving a request for information which includes an industry standard product identifier, processor(s) **202**

implementing information server **203** determine that the requested information page does not exist, and invokes an instance of mining agent **204** which recognizes the industry standard product identifier (ISPID) in the received request. Accordingly, instead of immediately replying to the requesting client that the requested information page is not available, mining agent **204** constructs and issues search commands to accessible resources to access and retrieve information associated with the product identified by the industry standard product identifier contained within the resource identifier of the received request. Mining agent **204** provides information server **203** with any information identified associated with the industry standard product identifier. In response to the request for the information page that does not exist, processor(s) **202** implementing information server **203** dynamically generate the instructions necessary to create the requested information page for provision to the requesting client including at least a subset of the information provided on the product requested by mining agent **204**. In one embodiment, the instructions generated and issued by processor(s) **202** and information server **203** is HTML code. In an alternate embodiment, the instructions generated and issued by processor(s) **202** and information server **203** is JAVA code, or ActiveX code.

In accordance with the teachings of the present invention, mining agent **204**, searches accessible databases for information associated with the industry standard product identifier received in a request for information from a remote client. In one embodiment, for example, mining agent **204** generates instructions with which to query the accessible databases and includes the industry standard product identifier received from the remote client via network

interface **208** and processor(s) **202**. In one embodiment, the search commands are SQL commands. In one embodiment, the information resource is a local database, wherein mining agent **204** issues the search command via processor(s) **202** and I/O port **210**. In an alternate embodiment, mining agent **204** employs common gateway interface commands in addition to

5 SQL search commands to access remote databases, e.g., database **118**, through a gateway server, e.g., server **117**. In one embodiment, mining agent **204** employs a hierarchical search of all accessible resources by first accessing local databases before accessing remote databases.

As alluded to above, in one embodiment, the search commands issued by mining agent **204** are SQL queries to a database. More specifically, mining agent **204** generates SQL commands including in one or more terms all or part of the industry standard product identifier parsed by and received from processor(s) **202**. In one embodiment, for example, mining agent **204** constructs and issues the following SQL command to retrieve information on property style, price, the number of bedrooms and baths for a particular property identified

10 by the ISPID in the received request:

SELECT style, price, beds, baths FROM properties WHERE mlsid=BC57402.

In an alternate embodiment, mining agent **204** constructs and issues the following SQL command to communicatively coupled information resources to retrieve information on vehicle model, style, color and price for the automobile identified by the ISPID in the

20 received request:

SELECT model, style, color, price FROM vehicle_stock WHERE vin=1J342M54789.

In one embodiment, the search conducted by mining agent **204** is typically completed during the window of latency commonly associated with the download of a web page from a remote server and, thus, with little to no perceptible delay to the end user. Thus, in accordance with the teachings of the present invention, a car dealership employing a server incorporating the teachings of the present invention effectively places their entire inventory on an accessible data network, wherein a customer simply enters a network address with the vehicle identification number (VIN) of the car of interest, and the server dynamically generates instructions to create the requested information page for provision to the requesting client. Accordingly, those skilled in the art will appreciate that the innovative server incorporating the teachings of the present invention may well be practiced in a number of alternate forms and embodiments without deviating from the spirit and scope of the present invention to enable vendors to make their products all the more accessible to clients, thereby increasing the number of leads and final sales.

Although depicted as executable code within storage medium **206**, those skilled in the art will appreciate that information server **203** and mining agent **204** may well take many alternate forms. In one alternate embodiment, for example, mining agent **204** is a separate functional block, embodied within an application specific integrated circuit (ASIC), a microcontroller, a special purpose processor, a software application and the like. Similarly, information server **203** may well be embodied as a special purpose processor, controller ASIC or PLD. Further, in alternate embodiments, the functionality of mining agent and information server **203** may well be embodied within a single functional element without

departing from the spirit and scope of the present invention. Accordingly, the foregoing example embodiments provided herein are to be regarded as illustrative and not exhaustive.

Given the foregoing architectural and functional descriptions of the first aspect of the present invention, those skilled in the art will recognize and appreciate the application of the present invention to network servers supporting e-commerce. Take, for example, a web site, i.e., a real estate information server. As alluded to above, prior art web sites supporting real estate databases typically required either a lengthy, uncomprehensible URL incorporating query strings, or multiple queries to identify and obtain information on a particular property, e.g., a first query to get to a realtor web site and a second query of their property database using, e.g., a multiple listing service (MLS) identifier for the property as a query term. A server incorporating the teachings of the present invention, however, will accept a data network request including the ISPID (e.g., the MLS identifier) in any of a number of alternate messaging protocols associated with the property for an information page, and selectively invoke mining agent 204 if the requested information page does not exist to search accessible information resources for information associated with the ISPID and reply by dynamically generating the instructions to create the requested information page for provision to the requesting client. That is, the teachings of the present invention facilitate the perception by the end user at the requesting client that each product identified by an industry standard product identifier has its own information site or information page when, in fact, such site or page does not necessarily exist prior to the server receiving the request.

Having introduced the architectural elements of the present invention with reference to **Figure 2**, the operation of the first aspect of the present invention will now be described with reference to **Figure 3**. However, for ease of explanation, and not limitation, the operation of a web server incorporating the teachings of the present invention will be developed in **Figure 3** with continued reference to **Figures 1 and 2**.

Accordingly, with reference to **Figure 3**, a method for managing the identification and dissemination of information content from an information server incorporated with the teachings of the present invention will be described within the context of an example information exchange. In particular, for purposes of explanation and not limitation, the teachings of the present invention will be described within the context of an example implementation wherein client **102** requests information from server **108** incorporating the teachings of the present invention in accordance with any of a number of messaging protocols. In accordance with one embodiment, for example, a user at a client computer issues a request for product information from server **108** incorporating the teachings of the present invention using the HTTP messaging protocol. In one embodiment, the request is in the form of a uniform resource locator (URL) comprising only a domain name and resource identifier comprised of an industry standard product identifier (ISPID). The request is passed to data network **106** via gateway server **104** to server **108**, which receives the request in block **302**. In particular network interface **208** of server **108** receives the request for information from communicatively coupled data network **106**, and passes the received request to processor(s) **202** which invoke an instance of information server **203**.

At block **303**, information server **203** determines whether the requested information page/directory identifier by the received request exists. If the requested information page/directory does exist, information server **203** provisions the instructions to create the requested information page/directory to the requesting client via processor(s) **202**, network
5 interface **208** and data network **106**, block **306**.

If, however, information server **203** determines in block **303** that the requested information page/directory does not exist, processor(s) **202** implementing information server **203** determine whether the received request includes a resource identifier comprised of an industry standard product identifier (ISPID), block **304**. In one embodiment, for example,
10 processor(s) **202** implementing information server **203** examine the request for information received in accordance with the HTTP protocol and determine whether the request includes an industry standard product identifier. One example of a request for information containing an industry standard product identifier is presented below in accordance with the HTTP messaging protocol, wherein an MLS identifier (real estate) is used to denote an web page:

15 <http://www.homelist.com/BC57402>

In accordance with the above HTTP example, www.homelist.com represents the domain name which uniquely identifies the target server (e.g., server **108**), while BC57402 is a resource identifier comprised of an ISPID denoting the requested information page, which in this example does not exist prior to receiving the request. In accordance with the teachings
20 of the present invention, however, processor(s) **202** implementing information server **203**, upon determining that the requested information page does not exist, determines that the

requested information page denotes an industry standard product identifier (MLS code) which uniquely identifies a particular property of interest. In an alternate embodiment, the industry standard product identifier may well be used to denote a domain name (e.g., a particular server). One example in accordance with the HTTP messaging protocol is

5 presented below, wherein an MLS identifier is used to denote a web site:

<http://BC57402.homelist.com>

In accordance with the above example, the ISPID is used to denote the domain, rather than a particular information page/directory.

If, in block 304, information server 203 determines that the received request does not include a resource identifier comprised of an industry standard product identifier, information server 203 generates and issues an appropriate response to the requesting client, block 312.

10

In one embodiment, information server 203 generates instructions to create a default information page for provision to the requesting client. In an alternate embodiment, information server 203 issues an error response for provision to the requesting client.

15 If, however, processor(s) 202 implementing information server 203 recognize that the received request includes a resource identifier comprised of an industry standard product identifier (ISPID), information server 203 passes the received ISPID to mining agent 204, which constructs and issues one or more query commands to accessible information resources, block 308. In one embodiment, mining agent 204 includes at least a subset of the

20 information contained within the received resource identifier, e.g., the ISPID, in the search command. In an alternate embodiment, mining agent 204 correlates the ISPID received in

the request to some other product identifier, which is used in the search command. In one embodiment, mining agent **204** issues the command to a local database, e.g., database **110** via I/O ports **210**. In alternate embodiments, mining agent **204** issues the search command to local and remote databases simultaneously via I/O ports **210** and network interface **208**, respectively. That is, if the requested information is not available from local sources, e.g., database **110**, mining agent **204** issues search commands to remote databases, e.g., database **118** via processor(s) **202**, network interface **208**, data network **106** and server **117**. One example embodiment of an information resource database is provided with reference to **Figure 6**.

Turning briefly to **Figure 6**, an example embodiment of a product database suitable for use in accordance with the teachings of the present invention is presented. In one embodiment, database **600** is suitable for use as local database **110** or remote database **118** in data network **100**. In accordance with the illustrated example embodiment, database **600** is shown comprising a number of data fields each containing information regarding a particular attribute of the product listed. In the illustrated example embodiment, product database **600** contains information regarding real estate. As shown, each of the properties listed are referenced by their unique industry standard product identifier, or MLS identifier, in field **602**. In fields **604** through **618**, various attributes of the product are listed for each of the properties identified in field **602**. In one embodiment, the listing agent **604**, architectural style **606**, price **608**, number of bedrooms and baths **610** and **612**, indication of air condition or garage **614** and **616** and the annual taxes are presented in product database **600**. Those

skilled in the art will appreciate that any of the product criteria listed in database **600** is searchable. Thus, while mining agent **204** generates search commands including the ISPID (i.e., the MLS identifier of database **600**), those skilled in the art will appreciate that other search terms may well be used without deviating from the spirit and scope of the present invention.

In block **310**, processor(s) **202** implementing an instance of mining agent **204** determines whether the search of accessible databases was successful, i.e., whether the requested information identified by the industry standard product identifier was available from local and/or remote information sources accessible from server **108**. In one embodiment, if the information is not accessible, mining agent **204** so informs processor(s) **202** and information server **203**, which issue an appropriate response to the requesting client **102**, block **312**. As provided above, in one embodiment information server **203** issues a response informing the user that the information is not available, block **312**. In an alternate embodiment, processor(s) **202** issue an invalid address response to the requesting client in accordance with the messaging protocol utilized. In alternate embodiments, processor(s) **202** and information server **203** may well generate and issue to the requesting client instructions to provision a default information page when the requested information is not available.

If the search of accessible resources conducted by mining agent **204** in block **310** is successful, mining agent **204** passes the retrieved information to processor(s) **202** implementing information server **203**, which generates instructions to create the requested information page for provision to the requesting client **102**, block **314**. That is not to say,

however, that processor(s) **202** implementing information server **203** wait until the search is complete to begin to provision the information page at the remote client **102**. In one embodiment, for example, processor(s) **202** begin issuing commands to requesting client **102** immediately, enabling a browser operating on client **102** to begin to render an information page within which the information on the product will be displayed once mining agent **204** receives a response from queried databases.

Those skilled in the art will appreciate, from the foregoing, that a server incorporated with the teachings of the present invention dynamically generates a custom information page in response to receiving a request including a resource identifier comprised of an ISPID for an information page/directory that may or may not exist, giving the end user the perception that each product identified by an ISPID has a dedicated information page when, in fact, it may not. The innovation herein described facilitates this perception of the end user, while enabling the commerce enterprise to utilize their preexisting product databases. Thus, the present invention represents an improvement in information management and content delivery by making product information more readily available without requiring wholesale changes in how such information is stored and maintained at the server.

Having described this first aspect of the present invention with reference to **Figures 1-3**, another aspect of the present invention will be described with reference to **Figure 5**. That is, **Figure 5** illustrates an example method for compiling and maintaining a statistical history of the marketing efforts resulting in requests of the information server **203**. In one embodiment, for example, a commercial enterprise utilizes different marketing codes in their

marketing literature when referencing a resource identifier for an information page/directory associated with a particular product. When an end user accesses the information using the denoted network address including the marketing code, processor(s) **202** implementing information server **203** invoke an instance of statistical database **205** incorporating the

5 teachings of the present invention to correlate the marketing code with the source marketing material and tracks the effectiveness of particular marketing materials.

Accordingly, with reference to **Figure 5**, the method begins as before when server **108** incorporating the teachings of the present invention receives a request for information from remote client **102**, block **502**. As described above, the request is received from data network

10 **106** via network interface **208** and processor(s) **202**. In block **504**, processor(s) **202** implementing information server **203** determine whether the received request includes a marketing code. In one embodiment, information server **203** recognizes any of a number of alternative separate marketing codes, as provided in **Table 1**, below. In one embodiment, information server **203** may well assume that any additional identifiers are marketing codes.

15 In alternate embodiments, information server **203** looks up the marketing code to correlate it with the marketing material in order to further refine and customize the information provisioned to the requesting client. In one embodiment, for example, information server **203** issues instructions to provision within the requested information page/directory a “thank you” for using the source marketing materials, e.g., a buyers guide.

Marketing Code	Corresponding Marketing Source
P	Print Media
AG #	A Particular Sales Agent
R	Radio Advertising

T	Television Advertising
I	Internet Advertising
BG	Buyers Guide (particular publication)

Table 1: Marketing Codes and Associated Sources

In accordance with the illustrated example embodiment, information server **203**

5 recognizes five (5) different marketing codes, one each associated with print advertising, sales person advertising/referrals, radio advertising, television advertising and Internet advertising.

Thus, an example request for information in accordance with the HTTP protocol might look

like the following URL: <http://www.homelist.com/BC54705BG>, which represents that the user requesting information on the product identified by ISPID BC57403 learned of the information

10 page through an advertisement in a particular publication, in this case a buyers guide. In the foregoing example embodiment, simple codes are used to illustrate the teachings of the present invention. Nonetheless, those skilled in the art will appreciate that marketing codes of greater or lesser complexity may well be used depending on the amount and detail of information the hosting enterprise requires. Accordingly, the use of marketing codes of greater or lesser

15 complexity in accordance with the teachings of the present invention is anticipated by the teachings herein.

If, in block **504**, it is determined that the received request for information does not

contain any marketing codes, the process continues with block **303** of the method illustrated in

Figure 3. Alternatively, if in block **504** processor(s) **202** implementing information server **203**

20 identify marketing codes in the received request, and invoke an instance of statistical database

205 which updates any of a number of statistics maintained regarding such marketing codes in block 506. In one embodiment, for example, processor(s) 202 implementing statistical database 205 update the database with information regarding the type of marketing code, when it was received, where it was received from, and the like. In one embodiment, once the marketing database has been updated, the process continues with block 303 of the method described above in **Figure 3**.

In accordance with one aspect of the present invention, a marketing evaluation report is automatically generated periodically by a server incorporating the teachings of the present invention. In one embodiment, the report generation function is a function of information server 203 selectively invoked by processor(s) 202. The frequency of such reporting is controlled by the hosting enterprise operating the server incorporating the teachings of the present invention, e.g., server 200. In one embodiment, server 200 automatically generates a marketing evaluation report on a periodic basis, e.g., a daily, weekly, monthly, quarterly or yearly basis. In an alternate embodiment, such evaluation reports may be automatically generated on demand. One example embodiment of an automatically generated marketing report is provided with reference to **Figure 7**.

As shown in **Figure 7**, server 200 automatically generates a marketing evaluation report 700 for the period identified in field 701 summarizing marketing information associated with several different marketing codes. In one embodiment, for example, marketing report 700 identifies several different statistics compiled and maintained by processor(s) 202 in accordance with information server 203 and statistical database 205. In one embodiment, for

example statistics on the effectiveness of product agents **702**, television advertising **704**, radio advertising **706**, Internet advertising **708** and print media **709**, are maintained with different summary information **710** for each. In one embodiment, the summary information **710** provided for each of the illustrated marketing codes includes the number of hits generated (e.g., the number of times a request for information is received by information server **203**), the number of requests for further information, requests for telephone call follow up and the price range of the products accessed using the particular marketing code. Accordingly, while agent **0** generated a large number of hits, those hits resulted in only 25 requests for telephone call follow up, while agent **112** only generated 250 hits to the web site, it resulted in 50 requests for follow up telephone calls. Just as the effectiveness of particular agent marketing can be compared and contrasted, so, too, can the effectiveness of different media, as television **704** can be compared to radio **706** and the Internet **708**. Those skilled in the art will appreciate that marketing report **700** is but one example, and that marketing reports with greater or lesser complexity may well be generated by server **200** without deviating from the spirit and scope of the present invention. For example, statistical analysis may well be employed to identify under performing marketing campaigns, cyclical changes in marketing effectiveness corresponding to season, etc.

In addition to the example embodiments presented above, an alternate embodiment of a server incorporating the teachings of the present invention is presented with reference to the block diagram of **Figure 4**. More specifically, **Figure 4** illustrates a block diagram of server **400** including the innovative mining agent **204** associated with one aspect of the present

invention introduced above. As shown, server **400** comprises processor(s) **402** with associated cache(s) **404**, bus bridge **410**, network interfaces **416**, memory subsystem **408**, video memory **406** and display device **407**, and mining agent **204** incorporated with the teachings of the present invention, coupled as shown. As with the embodiments presented above, mining agent

5 **204** is intended to represent any of a number of alternative embodiments, including embodiments wherein mining agent **204** is not a separate functional entity, but rather executable instructions stored on storage medium/device **208** and selectively executed by one or more of processor(s) **402**. In accordance with the teachings of the present invention, processor(s) **402** implementing the innovative information server, mining agent **204** and

10 accessible information resources cooperatively function to provide a requesting client with information associated with an industry standard product identifier (ISPID) received in a resource identifier of a request for an information page/directory and/or an information server.

In addition to those elements enumerated above, server **400** also includes storage medium/device **208**, read only memory **412**, keyboard and cursor control device **414** and

15 input/output (I/O) ports **417** communicatively coupling peripheral devices such as, for example, a hard copy output device **418** and/or database **110**. In one embodiment, server **400** is a computer system having a large amount of storage space (typically on the order of hundreds of gigabytes or terabytes), with multiple network interfaces **416** which support multiple simultaneous virtual connections between clients **102** and communicatively coupled

20 data networks, e.g., data network **106**. Accordingly, network interface **416** is intended to represent a number of alternative communication interfaces which enable server **400** to

communicate with remote clients via any of a number of alternative communication technologies. Except for the teachings of the present invention, described above, elements **402-418, 208** and **110** are representative of those commonly known in the art. Thus, those skilled in the art will appreciate that servers of greater or lesser complexity may well be substituted for server **400** without deviating from the spirit and scope of the present invention.

In another embodiment of the present invention, the teachings of the present invention for content management and delivery are embodied in software. Accordingly, **Figure 8** illustrates an example storage medium **800** having stored thereon machine executable instructions **802** which, when processed by a controller transforms an appropriately configured machine executing machine executable instructions **802** into a server incorporating the teachings of the present invention. In accordance with the illustrated example embodiment of **Figure 8**, storage medium **800** is intended to represent any of a number of alternative storage media including, but not limited to, floppy disks, magnetic tape, compact disk, digital versatile disk, optical disks, and the like. Further, those skilled in the art will appreciate that the machine executable instructions need not be located within the machine executing the instructions, but may be accessed from communicatively coupled devices.

In light of the foregoing, those skilled in the art will appreciate that the present invention not only provides for improved information management and delivery, but also includes innovative tracking and reporting features from which a host commercial enterprise can identify and quantify the source of referrals to the products supported by this innovative

server. In addition to the embodiments described above, those skilled in the art will appreciate that the teachings of the present invention may well be integrated within a single integrated circuit (not shown). That is, those skilled in the art will appreciate that advances in IC fabrication technology now enable complex systems to be integrated onto a single IC. Thus, in
5 accordance with one embodiment of the present invention, the teachings of the present invention may be practiced within an application specific integrated circuit (ASIC), programmable logic device (PLD), microcontroller, processor and the like.

While the many innovative features and aspects to the present invention have been described in terms of the above illustrated embodiments, those skilled in the art will
10 recognize that the invention is not limited to the embodiments described. The present invention can be practiced with modification and alteration within the spirit and scope of the appended claims. In particular, the present invention may be practiced with other features and/or feature settings. Particular examples of other features include but are not limited to transaction communication protocols and architectural attributes. Accordingly, the
15 description is to be regarded as illustrative instead of restrictive on the present invention.

Thus, alternate embodiments of the many innovative aspects of a method, apparatus and system for improved content management and delivery has been described.